

# ePMP™ 3000 Sector Antenna



Cambium Networks has deployed more than five million radios around the world achieving unparalleled degrees of scalability. Continuing the tradition of designing and manufacturing industry leading antenna solutions, the ePMP 3000 4X4 sector antenna encompasses all the key differentiations of the Cambium Antenna line and adds 4X4 Multi User MIMO Capability. Designed to work in 5 GHz spectrum and 90 degree coverage, the antenna is an integral part of the ePMP 3000 Access Point and allows for Multi User MIMO Operation.

## KEY DEPLOYMENT ADVANTAGES

- **Frequency Re-use:** Designed for ABAB channel re-use (two channels covering four sectors), the sector antenna has a minimum 30 dB front to back ratio over a wide rear facing aperture.
- **Channel Flexibility:** Consistent gain from 4.9 to 6.0 GHz allows the operator to select a channel anywhere in the band and achieve the expected performance.
- **Consistent Coverage:** Excellent null fill capabilities of the antenna allow for broad geographical coverage within a sector even near the base of the tower and the edges of the sector.
- **Designed for the Installer:** Small, compact design, integrated ePMP radio mount and GPS antenna integration.
- **Predictable Performance:** The sector antenna is integrated into Cambium Networks LINKPlanner. The 3D model shows coverage at all elevations and across the azimuth.

## KEY SPECIFICATIONS:

- 17 dBi gain
- 4.9 to 5.97 GHz spectrum
- 30 dBi front to back ratio
- IP 65 ruggedization

## SPECIFICATIONS





### ePMP 3000 SECTOR ANTENNA

Model Number	C050910D301A
Frequency Range	4.9 GHz to 5.97 GHz
Gain	17 dBi
3 dB Beamwidth - Azimuth	70 degrees
3 dB Beamwidth - Elevation	6 degrees
Electrical Downtilt	-2 degrees
Polarization	2X Horizontal, 2X Vertical

# SPECIFICATIONS

ePMP 3000 SECTOR ANTENNA	
Model Number	C050910D301A
Port-to-Port Isolation	> 20 dB
Front-to-Back Ratio	30 dB
Maximum Input Power	5 W
Input Impedance	50 ohms
Mounting Connectors	4 x RP SMA
Mounting Hardware	Included for mounting to mast diameters 2" to 4" (5 cm to 10 cm) -10 to +5 degree tilt Hardware included to connect ePMP access point to back of antenna body
Physical Dimensions	Antenna Body: 23.4" (H) x 9.6" (W) x 3.25" (D) (594 mm x 157 mm x 110 mm)
Weight	Antenna Body: 8.0 lbs, 3.7 kg w/ ePMP 3000 Access Point and Mounting Brackets: 13.8 lbs, 6.3 kg
Environmental	IP65
Radome Material	UV Protected ABS
Operating Temp	-40°C to 60°C (-40°F to 140°F)

# ANTENNA PATTERNS



# ANTENNA PATTERNS

